
MODERN FORMS





PRODUCT DESCRIPTION

As its name suggests, Hydra is all about water. Like all of our smart fans, it's wet-rated for outdoor use so you can maintain the continuity of your décor inside and out. Even with an impressive 120" blade sweep, this epically scaled smart fan moves a massive amount of air without consuming much energy, thanks to a powerful DC motor that runs up to 70% more efficient than AC motors. Control it all with our exclusive Modern Forms app. Available in 80 inches, 96 inches and 120 inches.

SPECIFICATIONS

Construction: Aluminum

Blade: 14° Pitch, 80" sweep, extruded aluminum

Downrod: 1" O.D. x 6"H included Mounting Slope: Up to 32°

Lead Wire: 80"

Hanging Weight: 43 lbs Total Power: 65.5W

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes BT wall control
- Additional BT wall control for 3, 4-way control sold separately
- Optional BT remote control with wall cradle sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

Light Source: LED Light Wattage: 23.5W **Dimming:** Integrated

Color Temperature: 3000K (2700K/3500K options available by special order)

Rated Life: 50,000 Hours

Standards: Title 24 JA8-2016 Compliant

ESTIMATED AIR PERFORMANCE

Airflow: 11308 cubic ft per minute on high

Power: 42 watts on high

Airflow Efficiency: 269 cubic ft per minute per watt Revolutions Per Minute: 88 RPMs on high Estimated Yearly Energy Cost (\$): \$6.09

WIRELESS PERFORMANCE

Bluetooth Range: Up to 150 ft* Wi-Fi Range: Up to 150 ft*

ORDER NUMBER

Model	LED Lumens	Delivered Lumens	Housing		Blade
FR-W1805-80L	2041	1013	BZ TT MB MW	Bronze Titanium Silver Matte Black Matte White	Bronze Titanium Silver Matte Black Matte White

Example: FR-W1805-80L-BZ

For 2700K add "-27" before the finish: FR-W1805-80L-27-TT

*Results may vary based on application and surroundings.













modernforms com Phone (866) 810.6615 (800) 526.2585 Headquarters/Fastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760



FR-W1805-80L



OPTIONAL ACCESSORIES								
- BT Wall Control	F-WCBT		White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.				
BT Remote Control	BT Remote Control F-RCBT		White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries.				
Wi-Fi Touch Panel Wall Control	F-TS	BK WT	Black White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.				
Downrod Couplers	XF-12 12ir XF-18 18ir XF-24 24ir XF-36 36ir XF-48 48ir XF-60 60ir XF-72 72ir XF-1	AS BA BZ CFI	Automotive Silver Brushed Aluminum Bronze Carbon Fiber** Dark Walnut Gloss Black Graphite Gloss White Koa†	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field. Connects two downrods together.				
Sloped Ceiling Kit	ped Ceiling Kit XF-SCK		Matte Black Matte White Oil Rubbed Bronze Stainless Steel Titanium Silver	Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.				

Examples: RF Wall Control - **F-WC-WT**, RF Remote Control - **F-RC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15′	14′	13'	12′	11'	10′	9′
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

**Carbon Fiber downrods available in 12", 18", 24" and 36"

†Koa downrods available in 12", 18", 24" and 36"

modernforms.comHeadquarters/Eastern Distribution CenterCentral Distribution CenterWestern Distribution CenterPhone (866) 810.661544 Harbor Park Drive1600 Distribution Ct1750 Archibald AvenueFax (800) 526.2585Port Washington, NY 11050Lithia Springs, GA 30122Ontario, CA 91760