CERVANTES

FR-W1806-56L

56" Ceiling Fan

DDERN FORMS



13" 13¾ -83/4' 56'

PRODUCT DESCRIPTION

Modern luxury is all about making life simpler- that's exactly what Cervantes does for you. With our Modern Forms app, you can map out schedules, optimize energy use and integrate with smart home devices you already own, like Amazon Alexa and Google Assistant. And Cervantes's clean, offset blades slice through the air with barely a whisper- that's because the powerful DC motor keeps things running smooth and super quiet. Available in versatile oil-rubbed bronze and graphite finishes.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- Includes Bluetooth remote control
- Optional wall control for 3, 4-way control sold separately
- · Compatible with Modern Forms app

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 2798/6577 Weighted-Average/High Energy Use (W): 13/29 **Estimated Yearly Energy Cost (\$):** \$3.24 Weighted-Average/High Efficiency (CFM/W): 211/227 Max RPM: 153

ORDER NUMBER

Model	Hous	sing	Blade				
FR-W1806-56L	GH	Graphite	WG	Weathered Gray			
	MB	Matte Black	BW	Barn Wood			
	OB	Oil Rubbed Bronze	DW	Dark Walnut			

SPECIFICATIONS

Construction: Aluminum, ABS Blade: 14° Pitch, 56" sweep 1" O.D. x 6"H included Downrod:

Mounting Slope: Up to 30° 80" **Hanging Weight:** 21 lbs **Total Power:** 48.5W

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20, Energy Star rated

125 x 30 sensorless DC motor **Motor Type:**

WIRELESS PERFORMANCE

Up to 150 ft* Wi-Fi Range: **Bluetooth Range:** Up to 150 ft

LUMINAIRE PERFORMANCE

Light Source: LED 19.5W **Light Wattage:** Lumens/Delivered): 1600/429 Dimming: Integrated CRI:

Color Temperature: 3000K (2700K/3500K options available)

Rated Life: 50,000 hours

Example: FR-W1806-56L-MB/BW

For 2700K add "-27"; for 3500K add "-35" before the finish: FR-W1806-56L27MBBW

*Results may vary based on application and surroundings.

*This fan comes uni-pack - blade select options are not available

The Modern Forms app synchronizes seamlessly with smart home devices you already own













modernforms.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

CERVANTES

FR-W1806-56L

56" Ceiling Fan



OPTIONAL ACCESSORIES

OF HONAL ACCESSORIES				
Bluetooth Wall Control		F-WCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	MACCOUNTS O	F-RCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Moder Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod		XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN		All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		XF-I		Connects two downrods together.
Sloped Ceiling Kit		XF-SCK		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control: F-WCBT-WT, Remote Control: F-RCBT-WT, Downrod: XF-12-BN, Downrod Coupler: XF-I-MB, Sloped Ceiling Kit: XF-SCK-MW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45° .

NOTE: Recommended maximum downrod length of 72" with 80" lead wire